

AC Type Antistatic Airgun with rotary Nozzle for Dust Removal and Ionisation

- World's first Integrated Ioniser Rotary Nozzle Airgun
- Most effective dust cleaning thanks to rotating nozzle with 6 tungsten ionising pins
- Compact, lightweight, ergonomic integrated ioniser
- Shockless design



Technical Information

Product	SE-ACG-55-RN-C2		SE-ACG-55-SN-C2		
Nozzle	Rotating Nozzle		Standard Nozzle		
Air Connection	10mm hose				
Air pressure - dry filtered air	3 bar		5 bar (7 bar max)		
Air Consumption (liter/min)	3bar		3bar	5bar	7bar
	110		168	224	270
Air push force	-		1.2N	1.9N	2.7N
Air flow speed (m/s)	-		10		
Power Unit	SE-PAC-55-4-C, SE-PAC-55-2-C, SE-PAC-80-4-C, SE-PAC-80-2-C				
Cable	3m. HFFR protected with HV connector. (up to 10m optional)				
Environment	0-60°C, %70rH max.				
Noise level	<40dBA				
Safety	Shockless, pin current <250µA, transformer current max 5mA (with fuse)				
Standards	2014/30/EU EMC Directive				
	2014/35/EU Low Voltage Directive				

Drawing / Dimensions

